

Recessed sequential thermostatic shower mixer

Ref. 790BOX-H9632

SECURITHERM mixer with no non-return valves in a waterproof housing



DESCRIPTION

Recessed sequential thermostatic shower mixer - Ref. 790BOX-H9632

SECURITHERM individual sequential thermostatic shower mixer. Opens/closes with cold water. No risk of cross flow between the hot and cold water. Mixer with no non-return valves on the inlets (reduces bacterial development). Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails. Securitouch thermal insulation prevents burns. Temperature control: cold water up to 39°C with maximum temperature limiter set at 39°C. Thermal shocks are possible. Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature. Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head. Hygiene control lever L. 100mm. M³/₄" inlets with integrated filters.

- Waterproof recessing housing behind a bright polished stainless steel cover plate 160 x 220mm.
- Adjustable recessing depth from 10 - 30mm.
- Order a wall-mounted outlet or shower head to complete.

10-year warranty.

TECHNICAL CHARACTERISTICS

Recessed sequential thermostatic shower mixer - Ref. 790BOX-H9632

Connector	M3/4"
Technology	SECURITHERM thermostatic single control
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Bright polished stainless steel
Norms	      
Warranty	

ADVANTAGES

-  Sequential, opens/closes with cold water
-  No non-return valves on the inlets
-  SECURITHERM: Optimal anti-scalding safety
-  Waterproof recessing housing

