

Sequential thermostatic shower mixer

Ref. H963015

SECURITHERM mixer with no non-return valve, bottom outlet



DESCRIPTION

Sequential thermostatic shower mixer - Ref. H963015

SECURITHERM thermostatic sequential shower mixer.
 Thermostatic sequential mixer: opens and closes with cold water.
 Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
 No risk of cross flow between hot and cold water.
 Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.
 Prevents cold showers: shuts off immediately if hot water supply fails
 Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.
 Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.
 Thermal shocks are possible.
 Body with smooth interior (reduces niches where bacteria can develop).
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and Hygiene control lever L. 100mm.
 M1/2" bottom shower outlet.
 Wall-mounted mixer with M1/2" M3/4" inline STOP/CHECK.
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Sequential mixer suitable for people with reduced mobility.
 Shower mixer with 30-year warranty.

ADVANTAGES



Sequential, opens/closes with cold water



No non-return valves on the inlets



SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H963015

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Length	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	
Warranty	
Repairability	

