




Geberit AquaClean Mera Comfort WC complete solution, wall-hung WC



Example image



APPLICATION PURPOSES

- For convenient and odourless toilet use
- For gently cleaning the anal and vaginal areas with water

CHARACTERISTICS

- Hybrid hot-water system with continuous flow heater and storage water heater
- Anal shower with double-nozzle WhirlSpray shower technology
- Separate Lady shower nozzle in protected resting position
- Adjustable shower water temperature
- Spray intensity can be set to five different levels
- Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Wall-hung
- Rimless WC ceramic appliance featuring TurboFlush flush technology
- Horizontal outlet
- Washdown WC with special glaze KeraTect
- User detection
- Odour extraction with ceramic honey comb filter can be activated

- Odour extraction unit with run-on function
- Dryer can be activated
- Dryer air intensity can be set to 5 positions
- Dryer arm can be extended
- Adjustable dryer temperature
- WC seat ring with rapid heating function
- Adjustable temperature of the WC-seat heating
- WC seat ring and WC lid with soft-closing mechanism
- WC lid with SoftOpening
- WC lid with quick release
- Touchless opening and closing of the WC lid
- Activation of the orientation light when approaching
- Orientation light can be set in seven colours
- Functions and settings via remote control
- Three user profiles can be programmed
- Compatible with Geberit Home App
- Water supply connection on the left, hidden behind the WC ceramic
- Mains connection with flexible three-core sheathed cable, on the right side, hidden behind the WC ceramic
- External water supply connection on the left possible with accessories
- External mains connection with power outlet on the right possible
- Premounted sound insulation
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077

TECHNICAL DATA

Degree of protection	IPX4
Nominal voltage	230 V AC
Mains frequency	50 Hz
Power consumption in standby mode max.	0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C
Water temperature, adjustment range	34–40 °C
Minimum flow pressure	0.5 bar
Calculated flow rate	0.03 l/s
Spray time	30–50 s
WC seat load max.	150 kg
Odour extraction unit	Yes
SoftOpening	Yes
With WC seat ring heating	Yes
With orientation light	Yes
With dryer functionality	Yes

SCOPE OF DELIVERY

- Water supply connection set for Sigma and Omega concealed cisterns 12 cm, installation height 112 cm
- Female socket for mains connection
- Spray shield

- Descaling agent, 125 ml
- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted holder and battery CR2032
- Fastening material

ACCESSORIES

- Wall-mounted control panel for Geberit AquaClean
- Interface module 12 V for Geberit AquaClean Mera/Sela
- Wall-mounted control panel, touchless, for Geberit AquaClean
- Interface module 4.1 V for Geberit AquaClean Mera / Sela
- Wall-mounted holder, large, theft-proof, for Geberit AquaClean remote controls (from year of manufacture 2024)

INFO

- This product is supplied with the Geberit AquaClean descaling agent. This consumable contains classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found at www.geberit.com.

Art. no.	Colour / surface	B cm	B1 cm	H cm	T cm	Protection class	Power consumption W	QuickRelease function
146.210.11.1	WC ceramic appliance: white / KeraTect Design cover: white / glossy	39.5	39.5	38	59	I	2000	Yes, WC seat ring and WC lid
146.210.21.1	WC ceramic appliance: white / KeraTect Design cover: chrome / glossy	39.5	39.5	38	59	I	2000	Yes, WC seat ring and WC lid