




# Geberit AquaClean Mera Classic WC complete solution, wall-hung WC



Example image



## APPLICATION PURPOSES

- For convenient and odourless toilet use
- For gently cleaning the anal and vaginal areas with water

## CHARACTERISTICS

- Hybrid hot-water system with continuous flow heater and storage water heater
- Anal shower with double-nozzle WhirlSpray shower technology
- Separate Lady shower nozzle in protected resting position
- Adjustable shower water temperature
- Spray intensity can be set to five different levels
- Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Wall-hung
- Rimless WC ceramic appliance featuring TurboFlush flush technology
- Horizontal outlet
- Washdown WC with special glaze KeraTect
- User detection
- Odour extraction with ceramic honey comb filter can be activated

- Odour extraction unit with run-on function
- Dryer can be activated
- Dryer air intensity can be set to 5 positions
- Dryer arm can be extended
- Adjustable dryer temperature
- WC seat ring and WC lid with soft-closing mechanism
- WC lid with SoftOpening
- WC lid with quick release
- Functions and settings via remote control
- Three user profiles can be programmed
- Compatible with Geberit Home App
- Water supply connection on the left, hidden behind the WC ceramic
- Mains connection with flexible three-core sheathed cable, on the right side, hidden behind the WC ceramic
- External water supply connection on the left possible with accessories
- External mains connection with power outlet on the right possible
- Premounted sound insulation
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077

## TECHNICAL DATA

Degree of protection	IPX4
Nominal voltage	230 V AC
Mains frequency	50 Hz

Power consumption in standby mode max.	0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C
Water temperature, adjustment range	34–40 °C
Minimum flow pressure	0.5 bar
Calculated flow rate	0.03 l/s
Spray time	30–50 s
WC seat load max.	150 kg
Odour extraction unit	Yes
SoftOpening	Yes
With WC seat ring heating	No
With orientation light	No
With dryer functionality	Yes

## SCOPE OF DELIVERY

- Water supply connection set for Sigma and Omega concealed cisterns 12 cm, installation height 112 cm
- Female socket for mains connection
- Spray shield
- Descaling agent, 125 ml
- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted holder and battery CR2032
- Fastening material

**ACCESSORIES**

- Wall-mounted control panel, touchless, for Geberit AquaClean
- Wall-mounted control panel for Geberit AquaClean
- Wall-mounted holder, large, theft-proof, for Geberit AquaClean remote controls (from year of manufacture 2024)

- Interface module 12 V for Geberit AquaClean Mera/Sela
- Interface module 4.1 V for Geberit AquaClean Mera / Sela
- WC seat ring, fixed, for Geberit AquaClean Mera Classic

**INFO**

- This product is supplied with the Geberit AquaClean descaling agent. This consumable contains classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found at [www.geberit.com](http://www.geberit.com).

<i>Art. no.</i>	<i>Colour / surface</i>	<i>B cm</i>	<i>H cm</i>	<i>T cm</i>	<i>Protection class</i>	<i>Power consumption W</i>	<i>QuickRelease function</i>
<b>146.200.11.1</b>	WC ceramic appliance: white / KeraTect Design cover: white / glossy	39.5	38	59	I	2000	Yes, WC seat ring and WC lid
<b>146.200.21.1</b>	WC ceramic appliance: white / KeraTect Design cover: chrome / glossy	39.5	38	59	I	2000	Yes, WC seat ring and WC lid