

Electronic sink mixer with BIOCLIP removable spout

Ref. 20871T3

Disposable, swivelling spout H. 300mm

DESCRIPTION

Electronic sink mixer with BIOCLIP removable spout - Ref. 20871T3

Electronic mixer for sinks and troughs with high, swivelling, removable BIOCLIP spout H. 300mm.

Supplied with 1 disposable, recyclable Hostaform® spout L. 180mm Ø 22mm.

Independent IP65 electronic control unit.

Mains supply with 230/12V transformer.

Flow rate limited to 7 lpm at 3 bar.

Chrome-plated solid brass body and base and reinforced fixing via 2 stainless steel rods.

Body and spout with smooth interiors (reduce niches where bacteria can develop).

Adjustable duty flush (pre-set flush for approximately 60 seconds every 24 hours after the last use) to prevent stagnation in the water supply if the system is not used for prolonged periods.

Thermal shocks are possible.

Shock-resistant infrared presence detection sensor.

Hygiene lever L. 100mm controls temperature.

PEX flexibles with and M3/8" solenoid valves.

Anti-blocking security.

Two shut-off options:

- Standard mode - timed flow with automatic shut-off;
- ON/OFF mode - user shuts off flow voluntarily or automatic shut-off after 30 minutes.

Position the sensor on the side of the mixer in On/Off mode.

10-year warranty.

TECHNICAL CHARACTERISTICS

Electronic sink mixer with BIOCLIP removable spout - Ref. 20871T3

Connector	M3/8"
Technology	Infrared presence detection sensor
Height	420mm
Drop height	300mm
Spout length	180mm
Flow rate	7 lpm
Finish	Chrome-plated brass
Norms	
Warranty	



ADVANTAGES



Automatic anti-bacterial proliferation duty flush



BIOCLIP spout for internal cleaning and descaling



Body & spout with smooth interiors reduce bacteria



Split delivery

