

## SECURITHERM shower panel

Ref. 79240015

Electronic battery-operated thermostatic

### DESCRIPTION

#### SECURITHERM shower panel - Ref. 79240015

Thermostatic electronic shower panel:  
 Aluminium epoxy-coated for surface mounting.  
 With top inlet via in-line stopcocks and Ø 15mm conical inlets.  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature: from cold water to 41 °C using the temperature control.  
 Anti-scalding safety: instant shut-off if cold water supply fails.  
 Thermal shocks are possible.  
 Battery-operated with 223 6V Lithium battery.  
 Infrared presence detection. Shower starts when hand is within 4cm of the sensor.  
 Shuts off on demand or automatically after 60 sec.  
 Duty flush (~60 sec. every 24hr after last use).  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated round shower head, vandal-resistant, scale-resistant with automatic flow rate regulator.  
 Concealed fixings, filters and non-return valves.  
 10-year warranty.

### TECHNICAL FEATURES

#### SECURITHERM shower panel - Ref. 79240015

Connector	M1/2" Ø 15mm
Technology	electronic
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Warranty	



### ADVANTAGES

-  Total hygiene: no manual contact
-  Duty flush limits bacterial proliferation
-  Thermostatic control
-  Instant shut-off if cold water supply fails

