

SECURITHERM shower panel

Ref. 79240015

Electronic battery-operated thermostatic



DESCRIPTION

SECURITHERM shower panel - Ref. 79240015

Thermostatic electronic shower panel:
 Aluminium epoxy-coated for surface mounting.
 With top inlet via in-line stopcocks and Ø 15mm conical inlets.
 SECURITHERM thermostatic mixer.
 Adjustable temperature: from cold water to 41°C using the temperature control.
 Anti-scalding safety: instant shut-off if cold water supply fails.
 Thermal shocks are possible.
 Battery-operated with 223 6V Lithium battery.
 Infrared presence detection. Shower starts when hand is within 4cm of the sensor.
 Shuts off on demand or automatically after 60 sec.
 Duty flush (~60 sec. every 24hr after last use).
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.
 Concealed fixings, filters and non-return valves.
 10-year warranty.

ADVANTAGES

-  Total hygiene: no manual contact
-  Duty flush limits bacterial proliferation
-  Thermostatic control
-  Instant shut-off if cold water supply fails

TECHNICAL FEATURES

SECURITHERM shower panel - Ref. 79240015

Connector	M1/2" Ø 15mm
Technology	electronic
Height	1045mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Warranty	

