



DB100-STL / DB125-STL

## DOLPHIN ELECTRONIC INFRARED TAP

- > **WRAS approved product**
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- > Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Flow rate - 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- > Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > Tap settings can be adjusted manually or by using remote control (DB51)
- > Mandatory Hygiene Flush feature can be specified to combat Legionella – please specify a time of ordering
- > 2 year manufacturer's warranty
- > Max water temperature 70°C
- > Operating pressure 0.5–8.0 bar (7–116 PSI)
- > Very low energy usage
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits

<b>HEIGHT</b>	<b>172 MM</b>
<b>DIAMETER</b>	<b>50 MM</b>
<b>PROJECTION</b>	<b>91 MM</b>

### PRODUCT CODES

#### BATTERY POWERED

- > Polished Chrome **DB100C-STL**
- > Brushed/Satin Chrome **DB100S-STL-2**

#### TRANSFORMER POWERED

- > Polished Chrome **DB125C-STL**
- > Brushed/Satin Chrome **DB125S-STL-2**