



DB840 / DB845

DOLPHIN ELECTRONIC INFRARED TAP

- › WRAS approved product
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Polished chrome plating or brushed nickel plating
- › Water Supply: Single inlet – cold or pre-mixed
- › A TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates available to special order – please enquire)
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- › 3/8" BSP water supply connector
- › Tap settings including optional hygiene flush can be adjusted by using remote control (DB51)
- › Mandatory Hygiene Flush feature can be specified to combat Legionella
- › 2 year manufacturer's warranty
- › Complies with SKA rating criteria
- › We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this DolphinBlue tap
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.

HEIGHT	157 MM
DIAMETER	45 MM
PROJECTION	122 MM

- › Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning)
- › Power connections: tap: female / power source: male
- › Maximum water temperature 70°C
- › Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- › Counter Hole: diameter 28-34mm
- › Minimum/maximum thickness: 2-27mm

PRODUCT CODES

BATTERY POWERED

- › Same product in brushed nickel plating **DB840S**
- › Same product in polished chrome **DB840C**

TRANSFORMER POWERED

- › Same product in brushed nickel plating **DB845S**
- › Same product in polished chrome **DB845C**