



DB100-STL / DB125-STL

DOLPHIN ELECTRONIC INFRARED TAP

- › **WRAS approved product**
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- › Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Flow rate - 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Tap settings can be adjusted manually or by using remote control (DB51)
- › Mandatory Hygiene Flush feature can be specified to combat Legionella – please specify a time of ordering
- › 2 year manufacturer's warranty
- › Max water temperature 70°C
- › Operating pressure 0.5–8.0 bar (7–116 PSI)
- › Very low energy usage
- › We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this tap
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.
- › Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
- › Power connections: soap dispenser: male / power source: female

HEIGHT	172 MM
DIAMETER	50 MM
PROJECTION	91 MM

PRODUCT CODES

BATTERY POWERED

- › Polished Chrome
- › Brushed/Satin Chrome

DB100C-STL
DB100S-STL-2

TRANSFORMER POWERED

- › Polished Chrome
- › Brushed/Satin Chrome

DB125C-STL
DB125S-STL-2