

# Jasper Morrison urinal, rim flushing, Fully Concealed

## ILLUSTRATED

- E6215** Jasper Morrison bowl urinal rim flushing, back inlet and concealed waste
- E6227** Urinal syphon connector with 75mm water seal, and 40mm outlet
- K7106** Urinal Connecting set
- A4188** Sensorflow 21 Electronic urinal flushing valve with concealing plate, mains

## OPTIONS

- A4189** Sensorflow 21 Electronic urinal flushing valve with concealing plate, link
- S6120** Urinal division Vitreous China with hanger and screw
- A4187** Sensorflow 21 urinal flush, battery, square panel mounted housing



## ILLUSTRATED PRODUCT DETAILS

### Weights

- E6215** 17.00 KG
- E6227** 0.50 KG
- K7106** 0.09 KG
- A4188** 1.90 KG

### Materials

- E6215** Vitreous China
- E6227** Plastic
- K7106** Plastic
- A4188** Chrome Plated Metal

### Finishes

- E6215**  White (01)
- E6227**  Neutral / No Finish (67)
- K7106**  Neutral / No Finish (67)
- A4188**  Stainless Steel Look (XJ)

### Designer

Jasper Morrison

### Standards

Vitreous china to BS 3402

### Special Notes

Please click the [Specify this] button and then configure the bowl by adding one of the Sensorflow 21 electronic urinal flushing products. Mains versions can power up to 5 link flushing valves or the battery versions can be independent. Please refer to Sensorflow 21 compact urinal flushing device pages. Then add as many urinals assembly types: mains/linked/battery, as needed in the room schedule. Not suitable for flushing from a cistern. Please note minimum working pressure required is 1 bar dynamic.

