

# TEMPOMATIC tap with BIOCLIP removable spout

Ref. 20804T215

Wall-mounted tap with stainless steel spout



## DESCRIPTION

**TEMPOMATIC tap with BIOCLIP removable spout - Ref. 20804T215**

Wall-mounted electronic tap with removable BIOCLIP spout for mounting on panels.

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Supplied with two removable BIOCLIP stainless steel spouts L. 129mm.

Base and spout with smooth interiors (reduces bacterial development).

Adjustable duty flush (pre-set at ~60 seconds every 24 hours after last use).

Flow rate limited to 4 lpm at 3 bar.

Separate sensor for mounting on panels.

Solenoid valve Ø 15mm for compression fittings with integrated filter.

Shock-resistant infrared presence detection sensor.

Ø 60mm chrome-plated brass base.

Anti-blocking security.

Recommended installation height: 110 - 200mm above the basin surface.

Suitable for people with reduced mobility.

10-year warranty.

Two shut-off options:

- standard mode: timed flow with automatic shut-off.

- ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.

Thermal shocks are possible.

## TECHNICAL CHARACTERISTICS

**TEMPOMATIC tap with BIOCLIP removable spout - Ref. 20804T215**

Connector	Ø 15mm
Technology	Electronic
Depth	190mm
Length	129mm
Spout length	129mm
Flow rate	4 lpm
Finish	Chrome-plated brass
Norms	
Warranty	

## ADVANTAGES



Automatic duty flush limits bacterial development



Hygiene: spout can be removed for disinfection



Hygiene: spout with smooth interior



Infrared detection with no manual contact