

SECURITHERM BIOCLIP thermostatic sink mixer

Ref. H9611P

Wall-mounted sequential mixer with stainless steel removable spout



DESCRIPTION

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611P

Wall-mounted SECURITHERM thermostatic sink mixer.
 Sequential: opens and closes with cold water.
 Supplied with 2 removable BIOCLIP stainless steel spouts L. 136mm.
 Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.
 Securitouch thermal insulation prevents burns.
 No risk of cross flow between hot and cold water.
 No non-return valves on the inlets.
 Scale-resistant sequential thermostatic cartridge.
 Temperature control: cold water up to 40°C. Temperature limiter set at 40°C.
 Thermal or chemical shocks are possible.
 Body and spout with smooth interiors and low water volume.
 Flow rate regulated at 7 lpm.
 No manual contact thanks to Hygiene control lever L. 146mm.
 Mixer with 150mm centres, supplied with in-line STOP/CHECK connectors ideal for hospitals.
 Chrome-plated brass body.
 10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611P

Connector	M1/2"
Technology	SECURITHERM BIOCLIP sequential, Securitouch
Height	141mm
Width	184mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	40°C
Finish	Chrome-plated brass
Norms	 
Warranty	

ADVANTAGES

-  Sequential: opens/closes with cold water
-  Hygiene: no non-return valves on the inlets
-  Hygiene: removable spout reduces bacterial development
-  SECURITHERM: optimum anti-scalding safety

