




Product	PLUS wash basin bracket with lever control, electrically height adjustable
Item number	<p>R4750 VVS:654003110 NRF:6132534 RSK:7972592 EAN:5708590309309 HMI: 71761 NBS:N13:30,335</p> 
Product description	<p>PLUS wash basin bracket, wall-mounted. Electrically height adjustable 300 mm with lever control. Lever control can be used as a towel rail and can be placed on either side of the wash basin. Recommendation: flexible feed/waste system R2065/R2067 (UK markets R2071/R2075). Incl. fixing bolts for wash basin (Recommended with MATRIX SMALL and MATRIX CURVE/NEW CURVE wash basins). Excl. fixing kit. See Technical datasheet (pdf) for information on fixings suitable for various wall types.</p>
Adjustability	Height adjustable
Adjustment height	300 mm
Product capacity	<p>Maximum load: 100 kg. Suitable for wash basins that weigh 16-22 kg. When the wash basin is loaded with 100 kg, each wall fastener will be carrying 42 kg. <i>Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position.</i> <i>Neither wash basin nor wash basin brackets are intended to carry a person, and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 100 kg and the wash basin weighs 20 kg, it is – according to ISO 17966 – the equivalent of a user weighing 106 kg leaning on the front edge of the wash basin.</i></p>





Product	PLUS wash basin bracket with lever control, electrically height adjustable
Speed, upwards	Speed up mm: 20 mm/s Speed down mm: 23 mm/s
Noise level	45 dB
Materials	The wash basin bracket is primarily made of 10-micrometre anodized aluminium. The ends of the bracket cover are capped with ABS polymer. The bracket is available with a lever control consisting of an ABS polymer switch at the end of an anodized aluminium arm.
Ergonomy	The height of the wash basin is easily adjusted by means of the lever control. The wash basin bracket suits all types of bolt-mounted wash basin. Its rounded, sleek design greatly facilitates cleaning.
Features	The arm that holds the lever control can function as a towel rail. The lever control can be placed on the right- or left-hand side of the wash basin. An independant user will be able to make the necessary adjustments to an electrically operated wash basin bracket themselves without any problems.
Mains connection (V)	230
Actuator (motor)	LA40 (Linak) 4000N, IPX6
Control box	SMPS14002
Power consumption (maximum load)	Power consumption by maximum load: 75 W Power consumption by standby: 1,5 W
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.










Product	PLUS wash basin bracket with lever control, electrically height adjustable
Cleaning	<p>PLUS & SELECT wash basin brackets. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p>DISINFECTANTS: Clinimax Difficil-S Erisan OXY+</p> <p>NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p>DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.</p>
Declaration of conformity	<p>This product complies with the requirements of Council Directive 93/42/EEC concerning medical devices, as last amended by Council Directive 2007/47/EC of 5 September 2007. It also complies with all relevant requirements in the Council Directive 2006/42/EC (of 17 May 2006) on machinery and the Council Directive 2011/65/EC on RoHS.</p>
Manufacturer	Pressalit A/S, Pressalitvej 1, 8680 Ry, Denmark










Product	PLUS wash basin bracket with lever control, electrically height adjustable
----------------	--

Installation in different wall types

	Concrete >B25 V8603 - Fixing kit, 4 coach screws Ø8 x 70, plugs SX10. To be ordered separately.
	Solid Brick >= Mz12 V8603 - Fixing kit, 4 coach screws Ø8 x 70, plugs SX10. To be ordered separately.
	Solid Sand Lime Brick >= Hlz12 V8603 - Fixing kit, 4 coach screws Ø8 x 70, plugs SX10. To be ordered separately.
	Aerated Concrete P4 V8653 - Fixing kit, 4 bolts M8 x 35, plugs FTP M 8. To be ordered separately.
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8603 - Fixing kit, 4 coach screws Ø8 x 70, plugs SX10. NB! Plugs are not needed. To be ordered separately.





Product	PLUS wash basin bracket with lever control, electrically height adjustable		
	<p>Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood</p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8 snaptight wingit</p> 	
	<p>Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)</p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8 snaptight wingit</p> 	
	<p>Drywall (2 x 12,5 mm) water-resistant</p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8 snaptight wingit</p> 