




<b>Product</b>	MATRIX manual basin unit	
<b>Item number</b>  <b>Colour</b>  <b>Product description</b>	R4825000 EAN:5708590349671 White MATRIX wash basin bracket, wall-mounted, with white installation cover and incl. concealed flexible feed/waste system and shallow trap. Manually height adjustable 200 mm with crank handle Incl. fixing bolts for wash basin (Can only be used with MATRIX MEDIUM wash basins, R2120/R2121). Materials: Powder-coated steel and polystyren Excl. fixing kit. See Technical datasheet (pdf) for information on fixings suitable for various wall types.	
<b>Adjustability</b>  <b>Adjustment height</b>  <b>Product capacity</b>	Height adjustable 200 mm Maximum load: 180 kg. Suitable for wash basins that weigh 25 kg. When the wash basin is loaded with 180 kg, each wall fastener will be carrying 72 kg. <i>Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position.</i> <b><i>Neither wash basin nor wash basin brackets are intended to carry a person, and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 180 kg and the wash basin weighs 25 kg, it is – according to ISO 17966 – the equivalent of a user weighing 206 kg leaning on the front edge of the wash basin.</i></b>	
<b>Materials</b>	Powder-coated steel and polystyren.	
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	










<b>Product</b>	MATRIX manual basin unit
<b>Cleaning</b>	<p>VALUE &amp; MATRIX wash basin brackets. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p><b>DISINFECTANTS:</b> Clinimax Difficil-S Erisan OXY+ Klorilli</p> <p><b>NON-DISINFECTANTS:</b> Suma Star free D1 Taski 100 Taski 200</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p>
<b>Declaration of conformity</b>	<p>This product complies with the requirements of Council Directive 93/42/EEC concerning medical devices, as last amended by Council Directive 2007/47/EC of 5 September 2007. It also complies with all relevant requirements in the Council Directive 2006/42/EC (of 17 May 2006) on machinery.</p>











<b>Product</b>	MATRIX manual basin unit
----------------	--------------------------

## Installation in different wall types

	<b>Concrete &gt;B25</b> V8605 - Fixing kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.
	<b>Solid Brick &gt;= Mz12</b> V8605 - Fixing kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.
	<b>Solid Sand Lime Brick &gt;= Hlz12</b> V8605 - Fixing kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately.
	<b>Aerated Concrete P4</b> V8655 - Fixing kit, 4 coach screws Ø10 x 70, plugs GB14, with grey screw covers. To be ordered separately.
	<b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood</b> V8605 - Fixing kit, 4 coach screws Ø10 x 70, plugs SX12, with white screw covers. NB! Plugs are not needed. To be ordered separately.





Product	MATRIX manual basin unit			
	<p><b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood</b></p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8</p> 	<p>snaptight</p> 	<p>wingit</p> 
	<p><b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)</b></p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8</p> 	<p>snaptight</p> 	<p>wingit</p> 
	<p><b>Drywall (2 x 12,5 mm) water-resistant</b></p> <p>Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>	<p>fischer KD 8</p> 	<p>snaptight</p> 	<p>wingit</p> 

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

