

**INSTALLATION (A)**

The Thrii unit is designed for front or rear service access. The unit is suitable for installation into brick, timber or metal pre fabricated wall types. To aid installation and ensure alignment within the aperture, the Thrii comes with a support frame and corner mounting threaded rods.

**ELECTRICAL (B)**

Power Ratings: 220–240 V 50 Hz, single phase, 2.6 to 3.1 kW (13 Amp fused double pole switched spur)

**WASTE (C)**

Connection pipe size of 1 ¼" (32mm). The unit should be connected to a deep seal waste trap.

**WATER (D)**

For optimum operation a dynamic water flow pressure of between 1 & 4 bar is required. Inlet connection on the unit support frame is 15mm push fit or ½" BSP FM. Connection to the mains water can be made with a Ø15 mm WRAS approved hose.

**SOAP**

There are 2 settings for soap delivery, LIQUID (default) or FOAM.

A range of liquid soaps are available from Wallgate.

**DIMENSIONS**

Weight: 29.4kg,

Unit Size: 450mm wide x 870mm high x 290mm depth. (Depth of 250 mm behind the panel is required).

An instruction leaflet is supplied with the product and the full operations manual is available via the Wallgate website.

**APPROVALS**



Flammability rating:

BS476-6 Fire propagation index = 4 (sub-index max = 4.2)

BS476-7 Class 1

Building Regulations 2010 Approved Document B: 2019 edition Class B-s3, d2 (formerly known as Class 0)

ISO EN 19712-3-2007 rated 5 for durability, stain resistance, cigarette burns, etc.

