

MODEL Thrii_ST HANDWASHER DRIER STAINLESS STEEL

SPECIFICATION SHEET

INSTALLATION (A)

The Thrii unit is designed for front or rear service access. The unit is fabricated in 304 grade stainless steel with a nylon coated die cast aluminium bowl. The unit is suitable for installation into brick, timber or metal pre fabricated wall types. To aid installation and ensure alignment within the aperture, the Thrii comes with a support frame and corner mounting threaded rods.

ELECTRICAL (B)

Power Ratings: 220–240 V 50 Hz, single phase, 2.6 to 3.1 kW (13 Amp fused double pole switched spur)

WASTE (C)

Connection pipe size of 1 ¼" (320mm). The unit should be connected to a deep seal waste trap.

WATER (D)

For optimum operation a dynamic water flow pressure of between 1 & 4 bar is required. Inlet connection on the unit support frame is 15mm compression for copper tube. Connection to mains water can be made with a ø15mm WRAS approved hose.

SOAP

There are 2 settings for soap delivery, LIQUID (default) or FOAM.

A range of liquid soaps are available from Wallgate.

DIMENSIONS

Weight: 23.6kg,

Unit Size: 450mm wide x 740mm high x 251mm depth. (Depth of 250 mm behind the wall or panel is required).

An instruction leaflet is supplied with the product and the full operations manual is available via the Wallgate website.

APPROVALS

