

# Anti-bacterial BIOFIL cartridge filter

Ref. 20050P.10P

Single use cartridge P, rain effect



## DESCRIPTION

### Anti-bacterial BIOFIL cartridge filter - Ref. 20050P.10P

Single use BIOFIL anti-bacterial cartridge P with sterilising grade of 0.1µm absolute-rated.

Filter cartridge with waterproof seal and with rain effect spray.

Hydrophilic polyethylene hollow fibres.

Filtration area: 1,400cm<sup>2</sup>.

Filtration flow rate: 12 lpm at 3 bar (filter only, excludes any flow rate restrictor/regulator in the shower).

Maximum upstream pressure at point-of-use: 5 bar.

Length of maximum use: 62 days after installation.

Compatible with and resistant to chemical and thermal shocks.

CE class 1 sterile anti-bacterial filters.

Weight: 80g.

Supplied in boxes of 10, individually wrapped, sterile.

## TECHNICAL CHARACTERISTICS

### Anti-bacterial BIOFIL cartridge filter - Ref. 20050P.10P

Technology	Terminal filter
Height	69mm
Length	Ø 58mm
Flow rate	12 lpm
Norms	

## ADVANTAGES



Guarantees water free from microorganisms



Quick and easy to install no need to isolate water



Lifespan: 62 days after installation

