

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741TP

Dual control thermostatic shower mixer



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP

Dual control SECURITHERM thermostatic shower mixer.
Mixer with anti-scalding safety: shuts off automatically if cold water fails.
Prevents cold showers if hot water supply fails.
Securitouch thermal insulation to prevent burns.
Scale-resistant thermostatic cartridge for temperature adjustment.
¼-turn ceramic head for flow rate adjustment.
Temperature adjusts from 25°C to 41°C.
Maximum temperature limiter pre-set to 38°C.
Thermal shocks are easy to undertake without shutting off the cold water.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and ERGO controls.
M1/2" shower outlet.
Filters and non-return valves built-in to inlets F3/4".
Mixer with inline STOP/CHECK connectors M1/2" M3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Depth	92mm
Length	286mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Norms	
Warranty	

ADVANTAGES



SECURITHERM: Anti-scalding safety



Securitouch thermal insulation prevents burns



Thermostatic: complete temperature stability



Pre-set maximum temperature limiter

