

Recessed thermostatic sequential shower mixer

Ref. H9631

SECURITHERM mixer with no non-return valves, kit 2/2







DESCRIPTION

Recessed thermostatic sequential shower mixer - Ref. H9631

Recessed thermostatic shower mixer, kit 2/2 :
Thermostatic sequential shower mixer: opens/closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial development).
No risk of cross flow between the hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.
Prevents cold showers: shuts off immediately if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature.
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.
ERGO controls.
M $\frac{3}{4}$ " inlets with integrated filters.
Order a wall-mounted outlet or shower head to complete.
Bright polished stainless steel cover plate 166 x 166mm.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer ideal for people with reduced mobility.
Shower mixer with 30-year warranty.
Order with waterproof recessing housing ref. H96BOX.

TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer - Ref. H9631

Technology	SECURITHERM Securitouch thermostatic sequential shower mixer
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	
Repairability	

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: total temperature stability

